

HOT SPOT® COLLECTION

PACE™



5

Seats

24

Jets

300

Gallons

Double
Lounge

Style

6'10" x 6'10" x 33"

Dimensions

115v/20 amp**

Voltage

HOT SPOT® COLLECTION

PACE™



Pace spa shown with Alpine White shell, Havana Cabinet and Havana Everwood step.

Spa Shell



Alpine White



Pearl



Pebble



Tuscan Sun

Cabinet



Almond



Havana



Storm

Spa Cover



Nutmeg



Stone

Seating Capacity	5 adults	Control System	IQ 2020® 115v/20 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 220v/50amp***, 60Hz
Dimensions	6'10" x 6'10" x 33" / 2.08m x 2.08m x 0.84m	Lighting (interior)	10 multi-color LED points of light, dimmable
Water Capacity	300 gallons/1,135 liters	Lighting (exterior)	4 multi-color LED points of light, dimmable
Weight	775 lbs./350 kg dry; 4,145 lbs./1,880 kg filled*	Heater	No-Fault® 1000w/115v, or 4000w230v
Spa Shell Options	Alpine White, Pearl, Pebble or Tuscan Sun	Energy Efficiency	FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Cabinet Options	Almond, Havana, or Storm	Effective Filtration Area	30 sq. ft., top loading
Jets - 24 (all with stainless steel trim)	3 XL Directional Hydromassage jets 2 Directional Hydromassage jets 2 Rotary Hydromassage jets 17 Directional Precision® jets	Vinyl Cover	3.5" to 2.5" tapered, 2 lb. density foam core Nutmeg or Storm
Jet Pump	Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque	Cover Lifter (Optional)	CoverCradle®, CoverCradle II, or UpRite®
Water Care System	FROG® In-Line Cartridge Ready	Steps (Optional)	Everwood® Step - Almond, Havana, or Storm Polymer Step - Ash
Ozone System (Optional)	FreshWater® III Corona Discharge	Entertainment System	Wireless Sound System

Actual colors and products may vary from print representation. See dealer to verify. * Includes water and 5 adults weighing 175 lbs. each. **Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

*** G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode. Export models available in 230v, 50Hz, 1000w heater.